

TCB

**GRANT OF EQUIPMENT
AUTHORIZATION**

TCB

Certification

**Issued Under the Authority of the
Federal Communications Commission**

By:

**Timco Engineering, Inc.
849 NW State Road 45
P.O. Box 370,
Newberry, FL 32669**

Date of Grant: 07/27/2009

Application Dated: 07/27/2009

**Holzberg Communications, Inc.
720 Totowa Road
P.O. Box PO Box 322,
Totowa, NJ 07511**

Attention: Andrew Holzberg , President/Owner

NOT TRANSFERABLE

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

FCC IDENTIFIER: Q9FDB-ANDY
Name of Grantee: Holzberg Communications, Inc.
Equipment Class: Licensed Non-Broadcast Transmitter
 Held to Face
Notes: TWO-WAY RADIO

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
EF	90	136.0 - 174.0	3.0	1.794 PM	11K0F3E
EF	90	136.0 - 174.0	3.0	1.868 PM	16K0F3E
EF	90	400.0 - 406.0	3.0	1.581 PM	11K0F3E
EF	90	400.0 - 406.0	3.0	1.615 PM	16K0F3E
EF	90	406.1 - 470.0	3.0	1.581 PM	11K0F3E
EF	90	406.1 - 470.0	3.0	1.615 PM	16K0F3E

Output Power listed is rated conducted. Maximum conducted output power is 3.56 Watts as allowed per 47 CFR, 90.205(s). This device must be restricted to work related operations in an Occupational/Controlled RF exposure Environment, not exceeding a maximum transmitting duty factor of 50%. All qualified end-users of this device must have the knowledge to control their exposure conditions and/or duration to comply with the Occupational/Controlled SAR limit and requirements. A label, as described in this filing, must be displayed on the device to direct users to specific training information for meeting Occupational Exposure Requirements. Body-worn operating configuration is limited to the specific belt-clip supplied for use with this product that provides at least 1.5 cm separation between the device and the users body. End-users must be informed of the body-worn operating requirements for satisfying RF exposure compliance.

The highest reported SAR values for this UHF Transmitter are - Head: 3.70 W/kg; Body-worn: 4.22 W/kg accounting for a 50% duty cycle.

EF: This device may contain functions that are not operational in U.S Territories except as noted in the filing. This grant has extended frequencies as noted in the filing and Section 2.927(b) applies to this authorization.

